TEHNICALDENT

Intrarea Sulfinei 94 Magurele, Ilfov. Tel: 021 312 56 60, E-mail: office@tehnicaldent.ro IBAN: RO17 RNCB 0068 0043 7192 0001 Nr. Inreg. Reg. Com.: J/09/137/99, Cod fiscal: RO 117 58 273

Autoclav 16 litri clasa N



Pret:

4.900,00 lei TVA inclusa

Descriere produs:

Autoclav clasa N (fara vacuum) destinat cabinetelor stomatologice, cabinetelor medicale, saloanelor de cosmetica.

Camera de sterilizare din otel inoxidabil, dintr-o singura bucata fara suduri sau imbinari, cu o durata de viata foarte indelungata!

Suport tavite si tavite integral fabricate din otel inoxidabil. Doua modalitati (directii) de plasate a suportului de tavite.

Modalitate foarta usoara de curatare a garniturii de usa.

Display digital al temperaturii cu o deviere a temperaturii setate de doar 0.5 C.

Putere de incalzire de 1800W, foarte puternica, pentru a face intreg procesul de sterilizare foarte rapid!

SFATURI SI INSTRUCTIUNI REFERITOARE LA AUTOCLAVUL CLASA N

Intrarea Sulfinei 94 Magurele, Ilfov. Tel: 021 312 56 60, E-mail: office@tehnicaldent.ro IBAN: RO17 RNCB 0068 0043 7192 0001 Nr. Inreg. Reg. Com.: J/09/137/99, Cod fiscal: RO 117 58 273

Date tehnice:

- Alimentare la priza 220V
- Putere 1800W
- Capacitate camera de sterilizare: 16 litri
- Timpi de sterilizare (excluzand preincalzirea): 121C (20 minute), 134C (6 minute)
- Dimensiune camera sterilizare: diametru 230 mm x 360 mm adancime
- Dimensiune produs: 440 x 575 x 370 mm



Intrarea Sulfinei 94 Magurele, Ilfov. Tel: 021 312 56 60, E-mail: office@tehnicaldent.ro IBAN: RO17 RNCB 0068 0043 7192 0001 Nr. Inreg. Reg. Com.: J/09/137/99 Cod fiscal: RO 117 58 273



PRODUCT FEATURES

SS304 chamber, one piece, without welding
SS304 tray and rack. The rack could be in two directions
Gasket is easy to be cleaned
Temperature digital display
Temperature deviation is less than 0.5°C
1800W heating elements, speed up the heating, more efficient

SEA-16L-B-LED

Basic Technical Data:
Voltage: 220V or 120V
Frequency: 50Hz/60Hz
Power: 1 800W
Chamber Capacity: 16L
European Class N
Sterilization temperature:
121 C/20min, 134 °C/6min
Chamber Size: Φ230x360mm
Product Size: 440X575X370 mm

